



4243 Gatecrest, Suite 103,
San Antonio TX 78217
(210) 368-9248

Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS ST/SG/AC.10/30/Rev6

Section 1 - Identification

Product Identifier: Power Steering Fluid Red

Supplier: MAXX Solutions

Supplier Phone: 210-368-9248

Supplier Address: 4243 Gatecrest, Suite 103, \
San Antonio TX 78217

Emergency Phone & Hours: 210-688-4966 24 hrs, 7 days/week

Intended Use Industrial Lubricant for use in enclosed systems.

Uses To Avoid Applications that generate oil mists in air.

Section 2 - Hazard Identification

Signal Word: WARNING

Other than flammability, no specific data exists for this mixture. Hazard classifications are calculated based on component information, according to GHS protocols for the relevant hazard.

Hazard Classifications: **Substance Or Mixture** Mixture
Eye damage/irritation (Category 2B),

Hazard Statements based on component information:

HAZARDS: Eye contact causes eye irritation.

Precautions:

Before handling, put on eye protection, approved organics respirator, face shield, chemical resistant gloves, and sleeves. Avoid breathing fumes or mists.

NO
PICTOGRAMS
APPLY

Other Hazards Not Resulting In Classification: May be hazardous to soil dwelling organisms.

Summary: Read entire SDS prior to use. Observe all precautions. Use engineering controls to minimize human exposure to workplace chemicals.



Power Steering Fluid Amber

Section 3 - Composition / Information on Ingredients

Component	CAS Number	% Range
HYDROTREATED PARAFFINIC DISTILLATE	64742-65-0	60 - 100
ADDITIVE MIXTURE	MIXTURE	5 - 15

Exact percentages and component identities are being withheld as trade secrets. Occupational Exposure Levels, Toxicity, and Ecological information on components is shown in Sections 8, 11, and 12 below. Users should read and understand the entire SDS. More specific information on components will be released to medical professionals in case of emergency.

Section 4 - First Aid Measures:

First responders should wear clothing appropriate for industrial exposure in accordance with local codes. At a minimum, all exposed skin should be covered, and latex gloves and eye protection meeting ANSI Z87 or CSA Z94.3 should be worn. First responders should avoid contact with spilled material. Spills of this material present a slip hazard. If smoke, fumes, or airborne mist is present, first responders should use organics respirator or self contained breathing apparatus.

IF SWALLOWED: Get immediate medical attention. Call poison control center.

IF INHALED: Remove affected person to fresh air and make comfortable for breathing. Get immediate medical attention.

IF IN EYES: Rinse eyes with water. Get immediate medical attention if irritation persists.

IF ON SKIN: Wash skin with cool water. Get medical attention if irritation persists.

IF ON CLOTHES: Do not allow skin contact with contaminated clothing. Remove contaminated clothing and wash before re-use.

IF EXPOSED: Contact physician if you feel unwell.

Most Important Symptoms ACUTE: Respiratory effects, vision effects. DELAYED: Dermatological effects.

Indication of Immediate Medical Attention Difficulty breathing, dizziness, extreme drowsiness, eye irritation, loss of vision, skin rash.



Power Steering Fluid Amber

Section 5 - Fire Fighting Measures:

Flash Point >93C

Hazardous Decomposition Products

Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of nitrogen, and heavy, acrid smoke.

Appropriate Extinguishing Media

Avoid spraying water jet on burning hydrocarbon liquids as this may spread the fire. Use dry chemical or foam extinguishing media.

Specific Fire Hazards

Fire fighters must be protected from smoke with self contained breathing apparatus. Heavy smoke may obscure vision. Smoke may contain oxides of carbon, nitrogen, sulfur, and chlorine.

Special Protective Actions

Use water spray to cool exposed containers.

Section 6- Accidental Release Measures:

Personal Precautions

Spills present a slip hazard. Extinguish/disconnect possible sources of ignition near spill. Ensure adequate ventilation of fumes from affected area. Remove unnecessary personnel from area around spill. Prior to cleaning up, don protective gear including chemical and hydrocarbon resistant outer layer, latex or rubber gloves, rubber boots, and eye protection. Emergency responders should wear chemical and hydrocarbon resistant gear.

Environmental Precautions

Small spills may be wiped up with rags. For spills >10 litres- if possible to safely do so, contain the spilled material using diatomaceous earth and/or absorbent pads. Dike drains and prevent material from entering sewers, ditches, drains, or water courses. Place absorbed material into sealed storage containers and consult an environmental expert for proper disposal measures. Immediately report any discharges that escape containment to the local environmental authority or fire department.

Methods for Cleaning Up

Absorption with diatomaceous earth and/or absorbent pads is best. Do not use vacuum. Do not wash hydrocarbon or chemical spills away into sewers or drains. Use proper disposal methods for spent absorbents and contaminated rags or clothing.

Section 7- Storage and Handling:

Precautions for Handling

Read and understand entire Safety Data Sheet prior to handling. Wear all appropriate protective gear prior to handling. Do not allow untrained personnel to handle this product. Handle with care to avoid spillage.

Methods for Safe Storage

Store only in original containers. Store containers indoors away from heat and flames. Store in secure location with good ventilation. Keep container sealed when not transferring product. Protect from rain and extreme cold. Avoid storage of hydrocarbons near strong mineral acids or materials marked 'Oxidizer'.



Section 8- Exposure Controls/Personal Protection:

Power Steering Fluid Amber

Control Parameters

No exposure limits are established for this mixture. Users should use lowest exposure value shown for components in this section.

Component Information - Occupational Exposure Limits:

HYDROTREATED PARAFFINIC DISTILLATE	US ACGIH: TWA: 5 mg/m3, STEL
ADDITIVE MIXTURE	No Known Hazard

Personal Protective Gear

Eye/Face Protection: ANSI Z87.1-1989 ; Gloves: Latex or Neoprene; Workers should wear safety glasses, gloves, long sleeves, long pants, hair covering, and oil resistant shoes, when handling this product.

Engineering Controls

Engineering controls should ensure adequate ventilation to keep airborne concentrations below threshold values shown above. Pumps and handling equipment should be designed to reduce human exposure potentials to liquids being transferred from containers into closed systems.

Section 9- Physical Properties

Appearance	Clear to Hazy Liquid	Upper Explosive Limit	Not Determined
Odor	Low Indescript	Lower Explosive Limit	Not Determined
Odor Threshold	No Data Available	Vapour Pressure	Negligible
pH	N/A oil based	Vapour Density	>1 (air=1)
Melting Point	Liquid under intended use conditions	Relative Density	0.8-0.9 kg/l 60C
Freezing Point	0 to -20	Solubility	Hydrocarbons, Alcohols
Initial Boiling Point	No Data Available	Partition Coefficient	Log KOW > 4 (mineral oil data)
Boiling Range	313C - 432C	Auto Ignition Temp	Not Determined
Flash Point	>93C	Decomposition Temp	Not Determined
Evaporation Rate	<1 (n-butyl acetate =1)	Viscosity cSt 40C	>20.5 cSt 40C



Section 10- Physical Properties:

Reactivity	May react violently if combined with strong oxidizers and heat.
Chemical Stability	Stable under recommended storage conditions.
Conditions to Avoid	Keep away from fire, sparks, and other sources of ignition.
Possibly Hazardous Reactions	None known.
Incompatible Materials	Strong acids and materials marked 'Oxidizer'.
Hazardous Decomposition Products	Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of nitrogen, and heavy, acrid smoke.

Section 11- Toxicological Information:

Symptoms of Exposure:

Likely Routes of Exposure	Dermal and/or Eye exposure from handling. Intended use of product is within enclosed systems which do not generate mist in air.
Ingestion	Ingestion of minimal amounts, e.g. failure to wash hands before eating/smoking, is unlikely to cause symptoms. Swallowing of liquid product may cause vomiting and nausea.
Inhalation	No symptoms are expected under intended use conditions. Exposure to concentrated fumes may cause transient hypoxia.
Dermal/Eye	Minimally irritating by dermal exposure. Eye exposure may cause transient stinging and blurred vision.
Immediate or Delayed Effects	Not expected from exposure to mineral or vegetable oils.
Interactive Effects	None Known

Numerical Measures of Toxicity - components (all LD/LC/EC 50 values shown below are based on animal or fish data) at max range value section 3.

Acute Oral Toxicity: HYDROTREATED PARAFFINIC DISTILLATE: Non Hazardous; ADDITIVE MIXTURE:

Acute Skin Toxicity: HYDROTREATED PARAFFINIC DISTILLATE: Non Hazardous; ADDITIVE MIXTURE:

Acute Toxicity Inhalation HYDROTREATED PARAFFINIC DISTILLATE: Non Hazardous; ADDITIVE MIXTURE:



4243 Gatecrest, Suite 103,
San Antonio TX 78217
(210) 368-9248

Power Steering Fluid Amber

Section 11- Toxicological Information: (continued)

Skin Corrosion: HYDROTREATED PARAFFINIC DISTILLATE: Non Irritating; ADDITIVE MIXTURE:

Eye Corrosion: HYDROTREATED PARAFFINIC DISTILLATE: Non-Categorized, Suspected Eye Irritant; ADDITIVE MIXTURE: Non-Categorized, Suspected Eye Irritant

Respiratory Sensitization: HYDROTREATED PARAFFINIC DISTILLATE: Non Sensitizing; ADDITIVE MIXTURE:

Skin Sensitization: HYDROTREATED PARAFFINIC DISTILLATE: Non Sensitizing; ADDITIVE MIXTURE: Cat 1 Sensitizer

Germ Cell Mutagenicity: HYDROTREATED PARAFFINIC DISTILLATE: No Hazard; ADDITIVE MIXTURE:

Carcinogen: HYDROTREATED PARAFFINIC DISTILLATE: No Hazard; ADDITIVE MIXTURE:

Reproductive Effects: HYDROTREATED PARAFFINIC DISTILLATE: No Hazard; ADDITIVE MIXTURE:

Power Steering Fluid Amber

Section 11- Toxicological Information: (continued)

Target Organ 1 Exposure: HYDROTREATED PARAFFINIC DISTILLATE: No Hazard; ADDITIVE MIXTURE:

Target Organ Multiple Exposure: HYDROTREATED PARAFFINIC DISTILLATE: No Hazard; ADDITIVE MIXTURE:

Aspiration Hazard: HYDROTREATED PARAFFINIC DISTILLATE: Cat 1 Aspiration Hazard; ADDITIVE MIXTURE:

Other Information No Other Information Available.

Section 12- Ecological Information:

- Ecological Summary** Hydrocarbon mineral oils, and non-petroleum oils, have low toxicity and are inherently biodegradable. See specific information below regarding aquatic toxicity data on components.
- Bioaccumulation** Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and have low bioaccumulation potential. Specific information on components is shown below.
- Persistence & Degradability** Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and are not persistent. OECD 301 values range from 50% to 95% in 28 days.
- Waste Treatment Effects** Product residues are not expected to enter publicly operated treatment works. No negative effects of this mixture are known.
- Soil Mobility** Mineral oils have been shown to adhere strongly to soil. Mobility is expected to be low.
- Other Adverse Effects** None Known

Toxicity to aquatic organisms, component information:

Aquatic Toxicity, Acute: HYDROTREATED PARAFFINIC DISTILLATE: Non Toxic; ADDITIVE MIXTURE:



Aquatic Toxicity, Long Term: HYDROTREATED PARAFFINIC DISTILLATE: No Chronic Aquatic Toxicity; ADDITIVE MIXTURE:

Ozone: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by 40 CFR 82, Subpt. A, App.A + 8.

Section 13- Disposal Considerations:

Disposal Containers & Methods Unused material is not a RCRA hazardous waste. Mixture with other wastes may cause classification as hazardous waste. Users must determine compliance with local, state, and federal regulations for proper classification and disposal of used oils and mixtures thereof. Suitable containers include steel and polyethylene drums and totes, for containment of used oil. Secondary containment is advised. Containers should be kept sealed and protected from rain and exposure.

Physical Chemical Properties Affecting Disposal Changes in physical and chemical properties during use, such as contamination with lead, zinc, or other metals, may affect classification for disposal. Used oils should be tested to determine metals content and applicable local, state, and federal regulations governing disposal of such fluids.

Improper Disposal Discharging of oily wastes into any sewer, watercourse, or unregulated drain is discouraged as improper and may result in fines, penalties, cleanup costs, and criminal liabilities for responsible parties.

Precautions for Landfill Oily liquid should not be disposed in a landfill. Disposal of oily absorbents, rags, or other items into a landfill should only be done with proper permission from local, state, and federal authorities.

Section 14- Transport Information:

US DOT 49 CFR Parts 171-180:

Proper Shipping Name Not Regulated **UN/ID/NA Number:** NA nonregulated

Transport Hazard Class NA **Packing Group** NA **Labels:** NA **ERGCode** NA

Marine Pollutant: No

IATA-DGR

IATA Proper Shipping Name Not Regulated **UN/ID Number** NA nonregulated

IATA Class NA **IATA Packing Group:** NA **IATA Labels** NA

IMDG-CODE

IMDG Proper Shipping Name Not Regulated

IMDG UN/ID Number NA nonregulated **IMDG Shipping Class** NA **IMDG Packing Group** NA

IMDG Labels NA **IMDG Marine Pollutant:** No

MARPOL 73/78 Annex II

MARPOL Not available for sale in bulk marine shipments

Special Precautions None



4243 Gatecrest, Suite 103,
San Antonio TX 78217
(210) 368-9248

Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS ST/SG/AC.10/30/Rev6

Power Steering Fluid Amber

Section 16- Other Information:

Revision Date 6/13/2019

Reasons For Revision

Sec 16 Other Info This Safety Data Sheet was prepared in good faith from the most recent information available, in accordance with ST/SG/AC.10/30/Rev.6. **HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.** No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.